

MEGAFLEX XL - XL DL BELT CHARACTERISTICS

STANDARD WIDTHS (inch)	050	075	100	150	200	300	400	600
STANDARD WIDTHS (mm)	12,7	19,05	25,4	38,1	50,8	76,2	101,6	152,4
Weight for standard belt (gr/m)	28	42	56	85	112	170	224	340
Weight for DL belt (gr/m)	32	47	63	95	127	190	253	380

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-0,5 mm

Standard thickness tolerance

+/-0,3 mm

Standard length

**from 1503,68 mm (1905 mm
with NFT) till 22768,56 mm**

Standard length tolerance



See page 29

Special version belt on request

See page 42

Tooth profile according ISO 5296-1

DL belt available only with standard steel, HF and stainless cord.



MEGAFLEX L - L DL BELT CHARACTERISTICS

STANDARD WIDTHS (inch)	050	075	100	150	200	300	400	600
STANDARD WIDTHS (mm)	12,7	19,05	25,4	38,1	50,8	76,2	101,6	152,4
Weight for standard belt (gr/m)	53	71	95	143	190	285	380	570
Weight for DL belt (gr/m)	50	75	100	150	200	300	400	600

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-0,5 mm

Standard thickness tolerance

+/-0,3 mm

Standard length

**from 1504,95 mm (1905 mm
with NFT) till 22764,75 mm**

Standard length tolerance


See page 29

Special version belt on request

See page 42

Tooth profile according ISO 5296-1

DL belt available only with standard steel, HF and stainless cord.



MEGAFLEX H - H DL BELT CHARACTERISTICS

STANDARD WIDTHS (inch)	050	075	100	150	200	300	400	600
STANDARD WIDTHS (mm)	12,7	19,05	25,4	38,1	50,8	76,2	101,6	152,4
Weight for standard belt (gr/m)	61	91	122	182	243	365	487	730
Weight for DL belt (gr/m)	66	99	132	197	263	395	527	790

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-0,5 mm

Standard thickness tolerance

+/-0,3 mm

Standard length

**from 1511,3 mm (1905 mm
with NFT) till 22758,4 mm**

Standard length tolerance


See page 29

Special version belt on request

See page 42

Tooth profile according ISO 5296-1

DL belt available only with standard steel, HF and stainless cord.



MEGAFLEX XH - XH DL

BELT CHARACTERISTICS

STANDARD WIDTHS (inch)	100	150	200	300	400	600
STANDARD WIDTHS (mm)	25,4	38,1	50,8	76,2	101,6	152,4
Weight for standard belt (gr/m)	267	400	533	800	1067	1600
Weight for DL belt (gr/m)	300	450	600	900	1200	1800

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/- 1 mm

Standard thickness tolerance

+/-0,5 mm

Standard length

**from 1511,3 mm (1911,35 mm
with NFT) till 22758,4 mm**

Standard length tolerance



See page 29

Special version belt on request

See page 42

Tooth profile according ISO 5296-1

DL belt available only with standard steel, HF and stainless steel cord.



MEGAFLEX T5 - T5 DL

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	10	16	25	32	50	75	100	150
Weight for standard belt (gr/m)	24	38	59	88	118	177	237	355
Weight for DL belt (gr/m)	27	44	68	87	137	205	274	410

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-0,5 mm

Standard thickness tolerance

+/-0,15 mm

Standard length

**from 1500 mm (1900 mm
with NFT) till 22770 mm**

Standard length tolerance



See page 29

Special version belt on request

See page 42

Tooth profile according DIN 7721-1

DL belt available only with standard steel, HF and standard stainless cord.



MEGAFLEX T10 - T10 DL

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	12	16	25	32	50	75	100	150
Weight for standard belt (gr/m)	60	80	125	160	250	375	500	750
Weight for DL belt (gr/m)	70	94	147	188	293	440	586	880

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-0,5 mm

Standard thickness tolerance

+/-0,3 mm

Standard length

**from 1500 mm (1900 mm
with NFT) till 22770 mm**

Standard length tolerance



See page 29

Special version belt on request

See page 42

Tooth profile according DIN 7721-1

DL belt available only with standard steel, HF and standard stainless cord.



MEGAFLEX T20 - T20 DL

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	25	32	50	75	100	150
Weight for standard belt (gr/m)	200	256	400	600	800	1200
Weight for DL belt (gr/m)	250	320	500	750	1000	1500

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-0,1 mm

Standard thickness tolerance

**+/-0,45 mm
from 1500 mm (1900 mm
with NFT) till 22760 mm**

Standard length


See page 29

Standard length tolerance

See page 42

Special version belt on request

Tooth profile according DIN 7721-1



DL belt available only with standard steel, HF and standard stainless cord.

MEGAFLEX AT5 - AT5 DL

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	10	16	25	32	50	75	100	150
Weight for standard belt (gr/m)	37	59	92	117	183	275	367	550
Weight for DL belt (gr/m)	43	68	107	137	213	320	427	640

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-0,5 mm

Standard thickness tolerance

**+/-0,2 mm
from 1500 mm (1900 mm
with NFT) till 22770 mm**

Standard length



See page 29

Standard length tolerance

See page 42

Special version belt on request

DL belt available only with standard steel, HF and standard stainless cord.



MEGAFLEX AT10 - AT10 DL

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	12	16	25	32	50	75	100	150
Weight for standard belt (gr/m)	72	97	150	190	300	450	600	900
Weight for DL belt (gr/m)	94	117	195	234	390	585	780	1170

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-0,5 mm

Standard thickness tolerance

**+/-0,3 mm
from 1500 mm (1900 mm
with NFT) till 22770 mm**

Standard length

See page 29

Standard length tolerance



Standard length tolerance for

+0/-1 mm/m

HP, HPF, HP stainless, kevlar

Special version belt on request

DL belt available only with standard steel, HF and standard stainless cord.



MEGAFLEX AT20 - AT20 DL

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	25	32	50	75	100	150
Weight for standard belt (gr/m)	250	320	500	750	1000	1500
Weight for DL belt (gr/m)	317	405	633	950	1267	1900

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-1 mm

Standard thickness tolerance

+/-0,45 mm

Standard length

**from 1500 mm (1900 mm
with NFT) till 22760 mm**

See page 29

Standard length tolerance

Standard length tolerance for



HP, HPF, HP stainless, kevlar

+0/-0,8 mm/m

Special version belt on request

See page 42

DL belt available only with standard steel, HF and standard stainless cord.



MEGAFLEX MTD5

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	15	20	30	50	85	100	150
Weight for standard belt (gr/m)	90	120	180	300	510	600	900

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

none

Standard cord

zinc plated steel

Standard width tolerance

+/-0,5 mm

Standard thickness tolerance

+/-0,3 mm

Standard length

**from 1504 mm (1904 mm
with NFT) till 22768 mm**


See page 29

Standard length tolerance

Special version belt on request

See page 42

Tooth profile according ISO 13050



MEGAFLEX RPP5 - RPP5 DL

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	10	15	25	30	50	85	100	150
Weight for standard belt (gr/m)	43	64	85	128	213	363	427	640
Weight for DL belt (gr/m)	47	71	118	142	237	402	473	710

Standard compound:

**white polyurethane
thermoplastic 92ShA**

Standard back cover

none

Standard tooth cover

Nylon fabric (NFT)

Standard cord

zinc plated steel

Standard width tolerance

+/-0,5 mm

Standard thickness tolerance

+/-0,2 mm

Standard length

1900 mm till 22770 mm

See page 29



Standard length tolerance

Special version belt on request

See page 42

Tooth profile according ISO 13050

DL belt available only with standard steel, HF and standard stainless cord.



MEGAFLEX RPP8 - RPP8 DL

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	15	20	30	50	85	100	150
Weight for standard belt (gr/m)	98	131	196	327	555	653	980
Weight for DL belt (gr/m)	110	147	220	367	623	733	1100

Standard compound:

**white polyurethane
thermoplastic 92ShA
none**

Standard back cover

Standard tooth cover

Standard cord

Standard width tolerance

Standard thickness tolerance

Standard length

Standard length tolerance

Special version belt on request

Tooth profile according ISO 13050

nylon fabric (NFT)

zinc plated steel

+/-0,5 mm



+/-0,3 mm

1904 mm till 22768 mm

See page 29

See page 42

DL belt available only with standard steel, HF and standard stainless cord.



MEGAFLEX RPP14 - RPP14 DL

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	25	40	55	85	115	150
Weight for standard belt (gr/m)	308	493	678	1048	1418	1850
Weight for DL belt (gr/m)	350	560	770	1190	1610	2100

Standard compound:

**white polyurethane
thermoplastic 92ShA
none**

Standard back cover

Standard tooth cover

Standard cord

Standard width tolerance

Standard thickness tolerance

Standard length

Standard length tolerance

Special version belt on request

Tooth profile according ISO 13050

Nylon fabric (NFT)

zinc plated steel

+/-1 mm



+/-0,4 mm

1904 mm till 22764 mm

See page 29

See page 42

DL belt available only with standard steel and standard stainless cord.



MEGAFLEX P2

BELT CHARACTERISTICS

STANDARD WIDTHS (mm)	25	50	75	100	150
Weight for standard belt (gr/m)	105	210	315	420	630

Standard compound:

**white polyurethane
thermoplastic 92ShA
none**

Standard back cover

Standard tooth cover

Standard cord

Standard width tolerance

Standard thickness tolerance

Standard length

zinc plated steel

+/-0,5 mm

+/-0,3 mm

from 1500 mm (1900 mm

with NFT) till 22770 mm

See page 29

See page 42

Standard length tolerance

Special version belt on request

